

## 1 Identification

- **Product identifier**
- **Trade name:** *40524 Low VOC Rubberized Undercoating*
- **Article number:** 40524
- **Relevant identified uses of the substance or mixture and uses advised against**  
*No further relevant information available.*
- **Application of the substance / the mixture** *Coating*
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
*SEM Products Inc.  
1685 Overview Drive  
Rock Hill, SC 29730  
803 207 8225*
- **Information department:**  
*cust\_care@semproducts.com : SEM Products, Inc. 1685 Overview Dr. Rock Hill, SC 29730 : phone 1-800-831-1122, M - TH 7am - 4pm EDT*
- **Emergency telephone number:** *CHEMTREC 1-800-424-9300*

## 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS02 Flame

*Flam. Liq. 2 H225 Highly flammable liquid and vapor.*



GHS08 Health hazard

*Muta. 1B H340 May cause genetic defects.*

*Carc. 1B H350 May cause cancer.*

*Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.*



GHS07

*Skin Irrit. 2 H315 Causes skin irritation.*

*Eye Irrit. 2A H319 Causes serious eye irritation.*

*STOT SE 3 H335 May cause respiratory irritation.*

- **Label elements**

· **GHS label elements** *The product is classified and labeled according to the Globally Harmonized System (GHS).*

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*

**Trade name: 40524 Low VOC Rubberized Undercoating**

(Contd. of page 1)

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.  
Talc

· **Hazard statements**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H335 May cause respiratory irritation.  
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1  
Fire = 3  
Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = \*1  
Fire = 3  
Reactivity = 0

· **Other hazards**

· **Results of PBT and vPvB assessment**

· **PBT:** Not applicable.  
· **vPvB:** Not applicable.

**3 Composition/information on ingredients**

· **Chemical characterization: Mixtures**

· **Description:**

Mixture: consisting of the following components.  
Weight percentages

· **Dangerous components:**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	30 - 40%
64742-89-8	Solvent naphtha (petroleum), light aliph.	13 - 30%
69430-35-9	Alicyclic hydrocarbon resin	7 - 10%
9017-27-0	Alpha-methyl styrene/vinyl toluene copolymer	7 - 10%

(Contd. on page 3)



Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 2)

14807-96-6	Talc	7 - 10%
66070-58-4	Styrene-Ethylene/Butylene-Styrene block Copolymer	5 - 7%

#### 4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**  
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

#### 5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

#### 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.  
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

#### 7 Handling and storage

- **Precautions for safe handling**  
No special measures required.  
Ensure good ventilation/exhaustion at the workplace.  
Open and handle receptacle with care.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**  
Keep ignition sources away - Do not smoke.

(Contd. on page 4)

Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 3)

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep receptacle tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

## \* 8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes and skin.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 4)

· Eye protection:



Tightly sealed goggles

## 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Liquid
Color:	According to product specification
· Odor:	Characteristic
· Odour threshold:	Not determined.

· pH-value: Not determined.

· Change in condition

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	139 °C

· Flash point: 10 °C

· Flammability (solid, gaseous): Not applicable.

· Ignition temperature: 455 °C

· Decomposition temperature: Not determined.

· Auto igniting: Product is not selfigniting.

· Danger of explosion: In use, may form flammable/explosive vapour-air mixture.

· Explosion limits:

Lower:	1.2 Vol %
Upper:	16.0 Vol %

· Vapor pressure at 20 °C: 14 hPa

· Density at 20 °C: 1.0461 g/cm<sup>3</sup>

· Relative density: Not determined.

· Vapour density: Not determined.

· Evaporation rate: Not determined.

· Solubility in / Miscibility with

Water: Not miscible or difficult to mix.

· Partition coefficient (n-octanol/water): Not determined.

· Viscosity:

Dynamic:	Not determined.
Kinematic at 20 °C:	100 s (DIN 53211/4)

· Solvent content:

Organic solvents: 30.1 %

(Contd. on page 6)



Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 5)

<b>VOC content:</b>	30.0 % 313.4 g/l / 2.62 lb/gl
<b>Solids content:</b>	69.9 %
<b>Other information</b>	No further relevant information available.

### 10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**  
The product shows the following dangers according to internally approved calculation methods for preparations:  
Irritant  
Carcinogenic.  
The product can cause inheritable damage.

- **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>		
14807-96-6	Talc	2B
1333-86-4	Carbon black	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

### 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

(Contd. on page 7)



Trade name: 40524 Low VOC Rubberized Undercoating



(Contd. of page 6)

- **Additional ecological information:**
- **General notes:**  
Water hazard class 2 (Self-assessment): hazardous for water  
Do not allow product to reach ground water, water course or sewage system.  
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

### 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

### 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT** Paint
- **ADR** 1263 Paint, special provision 640H
- **IMDG, IATA** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **ADR, IMDG, IATA**
- 
- **Class** 3 Flammable liquids
- **Label** 3
- **Packing group**
- **DOT, ADR, IMDG, IATA** III
- **Environmental hazards:**
- **Marine pollutant:** No

(Contd. on page 8)



Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 7)

· <b>Special precautions for user</b>	Warning: Flammable liquids
· <b>EMS Number:</b>	F-E,S-E
· <b>Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code</b>	Not applicable.
· <b>Transport/Additional information:</b>	
· <b>DOT</b>	
· <b>Quantity limitations</b>	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
· <b>Remarks</b>	ORM-D 49CFR 173.150,156,306
· <b>ADR</b>	
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>IMDG</b>	
· <b>Limited quantities (LQ)</b>	5L
· <b>Excepted quantities (EQ)</b>	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· <b>UN "Model Regulation":</b>	UN1263, Paint, special provision 640H, 3, III

**15 Regulatory information**

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

14807-96-6 Talc

67-56-1 methanol

· **TSCA (Toxic Substances Control Act):**

98-56-6 4-chloro-alpha,alpha,alpha-trifluorotoluene

64742-89-8 Solvent naphtha (petroleum), light aliph.

69430-35-9 Alicyclic hydrocarbon resin

9017-27-0 Alpha-methyl styrene/vinyl toluene copolymer

14807-96-6 Talc

66070-58-4 Styrene-Ethylene/Butylene-Styrene block Copolymer

1333-86-4 Carbon black

8042-47-5 White Mineral oil

6683-19-8 Tertrakis(methylene(3,5-di(tert)-butyl-4-hydroxyhydrocinnamate) ) methane

67-56-1 methanol

84633-54-5 Pentaerythritol tris tri ester with 3-(3,5-di-(tert)-butyl-4-hydroxyphenyl)propionic acid

(Contd. on page 9)



Trade name: 40524 Low VOC Rubberized Undercoating

(Contd. of page 8)

· **Proposition 65**

· **Chemicals known to cause cancer:**

1333-86-4	Carbon black
-----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

67-56-1	methanol
---------	----------

· **Carcinogenity categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value established by ACGIH)**

14807-96-6	Talc	A4
1333-86-4	Carbon black	A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

1333-86-4	Carbon black
-----------	--------------

67-56-1	methanol
---------	----------

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07 GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light aliph.  
Talc

· **Hazard statements**

H225 Highly flammable liquid and vapor.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H335 May cause respiratory irritation.  
H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
P241 Use explosion-proof electrical/ventilating/lighting/equipment.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 Store locked up.

(Contd. on page 10)



**Trade name: 40524 Low VOC Rubberized Undercoating**

(Contd. of page 9)

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **National regulations:**

· **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Environment protection department.

· **Contact:** Steve Gaver

· **Date of preparation / last revision** 08/14/2014 / 1

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organization

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

Muta. 1B: Germ cell mutagenicity, Hazard Category 1B

Carc. 1B: Carcinogenicity, Hazard Category 1B

STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

· **\* Data compared to the previous version altered.**