

PRODUCT HIGHLIGHTS

6737

Fisheye Remover

DESCRIPTION:

Transtar Fisheye Remover is an additive specially formulated to help avoid and prevent fisheyes. Fisheye Remover can be used with virtually all types of urethane and non-urethane 2K topcoats. Use for a smooth finish over surfaces that show evidence of fisheying usually due to contamination.

PRODUCTS:

6737 Fisheye Remover, 8 oz. (237 ml) Twin Neck Plastic Measuring Bottle, 6/case



SURFACE PREP:

See topcoat manufacturer's recommendations.



MIX RATIO:

Use 1/4 to 1/2 ounce per sprayable quart in Transtar 2K Clearcoats or Primers.

REDUCER:

See topcoat manufacturer's recommendations.



HVLP/LVLP:

See topcoat manufacturer's recommendations.



DRY TO SAND TIMES:

See topcoat manufacturer's recommendations.



SANDING:

See topcoat manufacturer's recommendations.

*See next page for more detailed product application. See website for this document in other languages.
Vea la página siguiente para un uso más detallado del producto. Vea el Web site para este documento en español.
Voir la prochaine page pour une application plus détaillée de produit. Voir le site Web pour ce document en français.*

PRODUCT DATA

6737

Fisheye Remover

SUITABLE SUBSTRATES:

See topcoat manufacturer for suitable substrates.

SURFACE PREPARATION:

See topcoat manufacturer for surface preparation.

APPLICATION & MIXING:

Use 1/4 to 1/2 ounce per sprayable quart in Transtar 2K Clearcoats or Primers.



TECHNICAL DATA:

APPEARANCE: Clear Liquid
% SOLIDS: 13.01 by weight
SHELF LIFE: One year (unopened)

ADVANTAGES:

- Prevents cratering and fisheyes
- Helps guard against silicone contamination
- Assures a smooth finish

COMPETITION:

DuPont Chroma Systems 259S
U-Tech MFEE4
Sherwin Williams AP395
Matrix MX01

Valspar 170
PPG Deltron/Concept DX73
Montana CR2ZFEEP
Standex Silistop

Glasurit 580-100
Rubberseal RS2500
Spies Hecker 8510

REGULATORY:

Category: Clear Coating 6737	Individual Component
VOC Actual	6.82#/gal (817 g/l)
VOC Regulatory (less water, less exempt compounds)	6.82#/gal (817 g/l)
Weight % of Volatiles	86.99
Weight % of Water	0
Weight % of Exempt Compounds	0
Volume % of Exempt Compounds	0
Density of Material	7.84#/gal

See website (www.tat-co.com) for this document in other languages.
Vea el Web site (www.tat-co.com) para este documento en español.
Voir le site Web (www.tat-co.com) pour ce document en français.